



# G-FORCE™

High-performance pressure washers combining reliability and performance with convenient user features.



CONTRACTOR

PROVEN QUALITY. LEADING TECHNOLOGY.

# Portable Pressure Washer

## G-Force 2525 LD

Excellent choice for your light to medium duty applications.

- 2500 psi (172 bar) at 2.5 gpm (9.5 lpm)
- 5.0 Honda GC series engine
- Radial axial pump with thermal protection
- 30 ft (9.1 m) hose
- Includes chemical injector and set of 3 tips — 0°, 15° and 40°
- **1 Year Limited Warranty**
- Instruction manual: 309828



		<b>G-Force 2525 LD</b>	
		246601	
<b>Operating Pressure</b>		2500 psi (172 bar, 17.2 MPa)	
<b>Engine</b> (4 cycle, air-cooled)		5.0 HP Honda GC Series	
<b>Fuel Tank Capacity</b>		1.82 qt (1.76 liter)	
<b>Water Pump Flow Rate</b>		2.5 gpm (9.5 lpm)	
<b>Pump Type</b>		Radial Axial	
<b>Weight</b>		70 lb (32 kg)	
<b>Dimensions</b>		Inches	22 w x 23.5 l x 34 h
		cm	(56 w x 60 l x 86 h)
<b>Tips</b>			
	0° Red	805419	
	15° Yellow	805420	
	40° White	805422	
	Chemical	805520	
<b>Instruction Manuals</b>		309828	

All Models Include: 30 ft (9.1 m) of non-marking high-pressure hose, gun and wand, 4 spray tips (0°, 15°, 40° and chemical), and 4 ft (1.2 m) chemical tube.

## Equipment Built to Last – Guaranteed!

G-Force Pressure Washers are built Graco tough to tackle all your cleaning jobs. You can count on the full G-Force line of Direct Drive and Belt Drive configurations to handle the most challenging job conditions.



### G4 Quality

- Every G-Force washer delivers Graco quality and dependability that you count on.
- Built in the U.S.A.

### G4 Performance

- Every G-Force washer is designed to deliver maximum performance in real world situations.
- Unmatched performance provides long life.

### G4 Warranty

- 3-year coverage against defects. (2525LD 1-year)
- Great warranty = peace of mind.

### G4 Productivity

- Excellent features make jobs go faster.
- No jobs are too big for the power of G-Force.

# Direct Drive Pressure Washers

## Tackles Your Toughest Cleaning Jobs!

Reliable, Contractor-Grade For Heavy-Duty Applications

- Performance levels contractors expect from Graco®
- Thermal relief valve prevents overheating and excessive packing wear
- Raised front bar for one-person, simple loading
- Convenient one-hand hose connection
- Upright cart design eliminates “ankle biting”
- Built-in tip storage includes all 5 quick connect sizes (0°, 15°, 25°, 40°, and chemical)



Slide-in Chemical  
Hose Connection



Convenient



Maximum Portability



	<b>G-Force 2730 B</b>	<b>G-Force 2730 H</b>	<b>G-Force 3030</b>	<b>G-Force 3340</b>	<b>G-Force 3540</b>
	244389	244390	244391	244392	244393
<b>Operating Pressure</b>	2700 psi (186 bar, 18.6 MPa)	2700 psi (186 bar, 18.6 MPa)	3000 psi (206 bar, 20.6 MPa)	3300 psi (227 bar, 22.7 MPa)	3500 psi (241 bar, 24.1 MPa)
<b>Engine</b> (4 cycle, air-cooled)	6.5 Briggs & Stratton OHV	6.5 HP Honda OHV	9.0 HP Honda OHV	11 HP Honda OHV	13 HP Honda OHV
<b>Fuel Tank Capacity</b>	3.8 qt (3.6 liter)	3.8 qt (3.6 liter)	6.2 qt (6.1 liter)	6.9 qt (6.5 liter)	6.9 qt (6.5 liter)
<b>Water Pump Flow Rate</b>	2.7 gpm (10.2 lpm)	2.7 gpm (10.2 lpm)	3.0 gpm (11 lpm)	3.5 gpm (13 lpm)	4.0 gpm (15 lpm)
<b>Pump Type</b>	General™ Pump, Triplex Piston, Ceramic Plunger	General Pump, Triplex Piston, Ceramic Plunger	General Pump, Triplex Piston, Ceramic Plunger	General Pump, Triplex Piston, Ceramic Plunger	General Pump, Triplex Piston, Ceramic Plunger
<b>Weight</b>	95 lb (43 kg)	99 lb (45 kg)	135 lb (61kg)	149 lb (69 kg)	149 lb (69 kg)
<b>Dimensions</b>	Inches cm	21.5 w x 35.5 l x 34 h (55 w x 90 l x 86 h)	21.5 w x 35.5 l x 34 h (55 w x 90 l x 86 h)	21.5 w x 35.5 l x 34 h (55 w x 90 l x 86 h)	21.5 w x 35.5 l x 34 h (55 w x 90 l x 86 h)
<b>Tips</b>					
0° Red	805535	805535	805539	805543	805543
15° Yellow	805536	805536	805540	805544	805544
25° Green	805537	805537	805541	805545	805545
40° White	805538	805538	805543	805546	805546
Set of 4 (0°, 15°, 25°, 40°)	244768	244768	244769	800708	800708
Blk Chemical Injector	805634	805634	805634	805634	805634
<b>Instruction Manuals</b>	309286	309286	309286	309286	309286

All Models Include: 50 ft ( 15.2 m) of non-marking, high-pressure hose, gun and wand, 5 spray tips (0°, 15°, 25°, 40° and chemical) and 8 ft (2.4 m) chemical tube.

# Belt Drive Pressure Washers

## Newly Designed – Lighter and Easier To Use!

High-Performance, Commercial-Grade for Severe-Duty Applications

- New lightweight cart without sacrificing durability
- Convenient tip holder on the handle
- Open frame design for easy access to engine and pump for adjustment
- EZ Start Valves for starting “under load” without triggering gun on recoil start models
- Heavy-duty, dual belts prevents downtime. Belts are long lasting and if one belt breaks, the equipment keeps running
- Reliable General™ pump with Triplex piston and ceramic plunger



Double Belt Design



EZ Start Valve



Spring Loaded Isolator



	<b>G-Force 3040</b>	<b>G-Force 3540</b>	<b>G-Force 4043</b>
	246454	246455	800707
<b>Operating Pressure</b>	3000 psi (206 bar, 20.6 MPa)	3500 psi (241 bar, 24.1 MPa)	4000 psi (276 bar, 27.6 MPa)
<b>Engine</b> (4 cycle, air-cooled)	11 HP Honda OHV Recoil Start	13 HP Honda OHV, Recoil Start	16 HP Briggs & Stratton OHV, V-Twin Electric Start
<b>Fuel Tank Capacity</b>	6.9 qt (6.5 liter)	6.9 qt (6.5 liter)	6 gal (23 liter) remote tank
<b>Water Pump Flow Rate</b>	4.0 gpm (15 lpm)	4.0 gpm (15 lpm)	4.3 gpm (16 lpm)
<b>Pump Type</b>	General™ Pump, Triplex Piston, Ceramic Plunger	General™ Pump, Triplex Piston, Ceramic Plunger	General™ Pump, Triplex Piston, Ceramic Plunger
<b>Weight</b>	199 lb (90 kg)	205 lb (93 kg)	255 lb (116 kg)
<b>Dimensions</b>	Inches cm	27 w x 46 l x 27 h (69 w x 117 l x 69 h)	27 w x 46 l x 27 h (69 w x 117 l x 69 h)
<b>Dimensions</b>		27 w x 46 l x 27 h (69 w x 117 l x 69 h)	49 w x 30 l x 26.5 h (125 w x 76 l x 67 h)
<b>Tips</b>			
0° Red	805547	805547	805543
15° Yellow	805548	805548	805544
25° Green	805549	805549	805545
40° White	805550	805550	805546
Set of 4 (0°, 15°, 25°, 40°)	800709	800709	800708
Blk Chemical Injector	805634	805634	805634
<b>Instruction Manuals</b>	309732	309732	308532

All Models Include: 50 ft ( 15.2 m) of non-marking high-pressure hose, gun and wand, 5 spray tips (0°, 15°, 25°, 40° and chemical), and 8 ft (2.4 m) chemical tube.

# Accessories

## Maximize Your Productivity!

### Rotating and Oscillating Tips

- 198012 Rotating Tip: 4000 psi (276 bar, 27.6 MPa) max. working pressure
- 198014 Rotating Tip: 5000 psi (344 bar, 34.4 MPa) max. working pressure
- 198013 Oscillating Tip: 5000 psi (345 bar, 34.4 MPa) max. working pressure

### Guns

- 244784 Standard Gun with vented composite wand handle and quick connect fittings
- 800429 Compensating Gun with lighter trigger pull
- 246674 Standard Gun, for use with the 2525 LD

### Extensions

- 116564 Telescoping Wand Extension: 18 ft (5.49 m), 4000 psi (276 bar, 27.6 MPa) max. working pressure
- 801134 Wand Extension: 32 in (81.2 cm) plated steel
- 801558 Wand Extension: 32 in (81.2 cm) stainless steel
- 803499 Wand Extension: 60 in (152.4 cm) aluminum
- 803500 Wand Extension: 96 in (243.8 cm) aluminum

### High-Pressure Hose

- 244783 3/8 in x 50 ft (10 mm x 15 m) non-marking hose with quick disconnects and swivel, 4000 psi (276 bar, 27.6 MPa). All G-Force except 2525 LD
- 118125 5/16 in x 30 ft (10 mm x 9.1 m) 3500 psi. Use only with the 2525 LD

### Wet Sandblasting

- 244766 Sandblasting Kit: Fittings, couplers, clamps, adapters, housing, sealant, and hose assembly (Sand blast tip not included)
- 800031 Sand Saver Adjustable Valve
- 805312 Sand Blast Tip: Fits the 2730 DD
- 805316 Sand Blast Tip: Fits the 3030 DD, 3340 DD, and 3540 DD
- 805317 Sand Blast Tip: Fits the 3040 BD, and 3540 BD
- 805313 Sand Blast Tip: Fits the 4043 BD

### Horizontal Surface Cleaner

- 116562 4000 psi (276 bar, 27.6 MPa) max. working pressure

### Couplers

- 801568 3/8 in (10 mm) OD(m) x 3/8 in (10 mm) npt(f) stem
- 801569 3/8 in (10 mm) OD(f) x 3/8 in (10 mm) npt(f) coupler

### Fluids

- 246377 Pump oil, 32 oz. Use only with Triplex Plunger Pumps — General Pump
- 117784 Pump oil, 4.5 oz. Use only with the G-Force 2525 LD — AR Pump



198012



244784



244783



244766



116562

## ABOUT GRACO

PROVEN QUALITY. LEADING TECHNOLOGY.

Founded in 1926, Graco is a world leader in fluid handling systems and components. Graco products move, measure, control, dispense and apply a wide range of fluids and viscous materials used in vehicle lubrication, commercial and industrial settings.

The company's success is based on its unwavering commitment to technical excellence, world-class manufacturing and unparalleled customer service. Working closely with qualified distributors, Graco offers systems, products and technology which set the quality standard in a wide range of fluid handling solutions. Graco provides equipment for spray finishing, protective coating, paint circulation, lubrication, and dispensing sealants and adhesives, along with power application equipment for the contractor industry. Graco's ongoing investment in fluid management and control will continue to provide innovative solutions to a diverse global market.

## GRACO HEADQUARTERS

### AMERICAS

MINNESOTA  
Worldwide Headquarters  
Graco Inc.  
88-111th Avenue N.E.  
Minneapolis, MN 55413

MAILING ADDRESS  
P.O. Box 1441  
Minneapolis, MN 55440-1441  
Tel 612 623-6000  
Fax 612 623-6777

### EUROPE

BELGIUM  
European Headquarters  
Graco N.V.  
Industrieterrein - Oude Bunders  
Slakweidestraat 31  
3630 Maasmechelen, Belgium  
Tel 32 89 770 700  
Fax 32 89 770 777

### ASIA PACIFIC

JAPAN  
Graco K.K.  
1-27-12 Hayabuchi  
Tsuzuki-ku  
Yokohama City, Japan 2240025  
Tel 81 45 593 7300  
Fax 81 45 593 7301


CHINA  
Graco Hong Kong Ltd.  
Representative Office  
Room 118 1st Floor  
No. 2 Xin Yuan Building  
No. 509 Cao Bao Road  
Shanghai, P.R.China 200233  
Tel 86 21 649 50088  
Fax 86 21 649 50077

KOREA  
Graco Korea Inc.  
Choheung Bank Building,  
4th Floor #1599,  
Gwanyang-Dong, Dongan-Ku,  
Anyang-Si, Gyunggi-Do,  
Korea 431-060

Tel 82-31-476-9400  
Fax 82-31-476-9801

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Graco Inc. is registered to I.S. EN ISO 9001



### Sales/Distribution/Service North America

800-690-2894  
FAX 800-334-6955  
WWW.GRACO.COM

GRACO INC.  
P.O. Box 1441  
Minneapolis, MN 55440-1441

