

XTR™ Airless Spray Guns

Built for Extreme Conditions



Graco's NEW XTR Airless Spray Guns are the ideal choice for high solids and plural-component coatings. The compact, lightweight design offers flexibility in hard to reach places and is ideal for spraying primers, epoxies, urethanes and fire retardant coatings.

- Compact design allows for easy maneuverability
- Maximum fluid pressure of 7250 psi (500 bar, 50 MPa)
- Variety of handle and trigger options
- High quality materials and construction



Call 1-877-844-7226 for more information about the NEW Graco® XTR Gun.

Email us at info@graco.com or visit our website at www.graco.com/protectivecoatings

Needle Assembly and GHD RAC™ SwitchTip™

- Designed for maximum performance with high solids coatings and high pressure output
- Factory set needle - no adjustments necessary for smooth control
- Consistent shut-off with less restriction and better fluid flow
- Longer life needles help eliminate stick and spitting
- Exceptional life, pattern and finish

Trigger Guard

- Easily detaches from gun for easy access to tip guard
- Acts as a wrench to aid in filter removal from gun handle
- Small profile to spray in tight areas



Variety of Handle and Trigger Options

- Oval-insulated or round handle for operator preference
- Lightweight trigger pull
- 2-and 4-finger trigger options

Easy Out™ Gun Filter

- Designed to filter paint inside out for reduced tip plugs
- Eliminates collapsed filters
- Provides more filtration area than competitive airless guns

NEW! EasyGlide™ Swivel

- Allows easier gun movement under high pressure

Technical Specifications

Maximum fluid working pressure	7250 psi (500 bar, 50 MPa)
Fluid orifice	0.090 in (2.3 mm)
Fluid inlet	1/4 npsm
Maximum fluid temperature	160° F (71° C)
Sound pressure	103dB(A)*
Sound power	111.6dB(A)*
Wetted parts	Stainless steel, polyethylene, polyurethane, polypropylene, nylon, acetal, carbide
Instruction Manual	310743

* Results are maximum readings taken at 6000 psi (414 bar, 41 MPa), with HD427 tip, using water. Sound power level was tested to ISO 3744-1981.

Accessories

287450	2-finger trigger kit
287449	4-finger round trigger kit
287451	4-finger oval insulation trigger kit
246294	10 in (254 mm) gun extension, 7250 psi (500 bar, 50 MPa)
246295	15 in (380 mm) gun extension, 7250 psi (500 bar, 50 MPa)
246296	18 in (457 mm) gun extension, 7250 psi (500 bar, 50 MPa)
246297	180° spray nozzle, 7/8-14 UNC-2B, 7250 psi (500 bar, 50 MPa)
248837	Gun repair kit, includes gasket, needle and seat
245994	GHD tip guard kit
287032	Filter, 60 mesh
287033	Filter, 100 mesh
287034	Filter, 60 and 100 mesh combination

Whip Hose

214912	3 ft (0.91 m), 1/4 npsm(fbe), 5000 psi (345 bar, 34.5 MPa)
238383	6.5 ft (2 m), 1/4 npsm(fbe), 5000 psi (345 bar, 34.5 MPa)
246193	6 ft (1.8 m), 1/4 npsm(fbe), 8000 psi (550 bar, 55 MPa)

Dimensions

Weight	24 oz (688 g)
Length	4.35 in (111 mm)
Height	7.1 in (180 mm)

Ordering Information

XTR-7 Airless Spray Gun

248609	Round handle, four-finger trigger, GHD tip guard, NO TIP
248610	Round handle, four-finger trigger, 519 flat tip
248611	Oval-insulated handle, four-finger trigger, 519 GHD RAC tip
248612	Oval-insulated handle, two-finger trigger, 519 GHD RAC tip
248613	Round handle, four-finger trigger, 519 GHD RAC tip
248614	Round handle, two-finger trigger, 519 GHD RAC tip

Fluid Hose - 5000 psi (345 bar, 34.5 MPa)

214915	1/4 in ID x 50 ft (6.3 mm x 15.2 m), 1/4 npsm(fbe)
238395	3/8 in ID x 24.6 ft (9.5 mm x 7.5 m), 3/8 npt(m) x 3/8 npsm(f)
238396	3/8 in ID x 49.2 ft (9.5 mm x 15 m), 3/8 npt(m) x 3/8 npsm(f)
238397	3/8 in ID x 98.4 ft (9.5 mm x 30 m), 3/8 npt(m) x 3/8 npsm(f)
238716	1/2 in ID x 24.6 ft (12.7 mm x 7.5 m), 1/2 npsm(fbe)
238717	1/2 in ID x 50 ft (12.7 mm x 15.2 m), 1/2 npsm(fbe)
238718	1/2 in ID x 98.4 ft (12.7 mm x 30 m), 1/2 npsm(fbe)

Fluid Hose - 7400 psi (510 bar, 51 MPa)

237071	1/4 in ID x 49 ft (6.3 mm x 15 m), 1/4 npsm(fbe)
237072	3/8 in ID x 49 ft (9.7 mm x 15 m), 3/8 npsm(fbe)

Fluid Hose - 7970 psi (550 bar, 55 MPa)

237213	1/2 in ID x 49 ft (12.7 mm x 15 m), 1/2 npsm(fbe)
---------------	---

